



A Five Star Compactor



## The K100 Marine Compactor

- ◆ Produces bag containing 40 – 100 lbs (18 – 45 kg)
- ◆ Optional larger bin capacity 100 – 250 lbs (45 – 113 kg), uses larger bags
- ◆ Unique design for bagging and/or baling waste material
- ◆ Refrigerator style door opening to container for easy bag removal
- ◆ Provision for multiple containers for various compaction/recycle applications
- ◆ AISI stainless steel cabinet, wash down motor and all containers
- ◆ All doors sealed for marine use
- ◆ All hydraulic and electrical components contained in upper cabinet.



Stainless Steel version not pictured

### TECHNICAL SPECIFICATIONS

Compactor	Dimensions	Loading Aperture	Size
<b>Height</b>	71" (1790mm)	<b>Height</b>	18" (457mm)
<b>Width</b>	33.5" (850mm)	<b>Width</b>	28.5" (724mm)
<b>Depth</b>	28" (711mm)	<b>Filled Bag Dimensions &amp; Container Capacity</b>	
<b>Weight</b>	1175 lbs (533kg)	<b>Height</b>	25" (635mm)
<b>Compaction Force</b>	5,200 lbs (2,359kg)	<b>Width</b>	29" (736.6mm)
<b>Noise Level</b>	70-72 Decibels	<b>Depth</b>	25" (635mm)
<b>Power Supply</b>	240-480/600V 3-phase optional	<b>Weight</b>	40-100 lbs (18-45 kg)
<b>Cylinder Stroke Length</b>	32 inches (813mm)	<b>Container Capacity</b>	.39 cu yds (.30 cu meters)
<b>Motor</b>	2 HP multi-tap Voltage	<b>Cycle Time</b>	32 Seconds

### Features of the K100 Marine Compactor

- ◆ Can also bale material
- ◆ Small footprint
- ◆ Compaction ratio: 6 -12:1
- ◆ Easy to remove bag with hand cart
- ◆ Meets or exceeds safety standards
- ◆ No exposed pinch points
- ◆ Easy to clean with swing out doors
- ◆ Bi-lingual safety decals
- ◆ One year warranty on all parts
- ◆ Approval Ratings: ETL and ANSI
- ◆ Automatic shut down if door opened
- ◆ Low noise level
- ◆ Low operating costs
- ◆ Simple and safe to use
- ◆ Competitively priced