



## Bin RotoPac Compactor

Toll Free 888-353-6229



=



10 Cubic Yards

1.6 cu yd Bin RotoPac

### Maximum Compaction, Minimum Footprint

<b>Dimensions</b>	86.5" x 51" x 61" (220 cm x 130 cm x 155 cm)	<b>Manufactured by:</b>	KenBay, PO Box 242, Mendham NJ 07945 Tel. 973-543-3200 <a href="http://www.kenbay.com">www.kenbay.com</a>
<b>Working</b>	119" x 51" x 61" (302 cm x 130 cm x 155 cm)	<b>Electrical</b>	240/480v 3-phase 14amp/7amp 5 HP (4 kw) Electric motor, 50/60 hertz 24V A.C. Control Circuit Voltage
<b>Loading Height</b>	58" (147 cm)	<b>Torque</b>	4,400 ft-lbs at compaction drum surface
<b>Weight Bin Volume</b>	2,690 lbs (1,220 kgs) 1.6 cubic yd (1.2 cubic m)	<b>Front Loading Bin</b>	82"x47"x37" (206 cm x 119 cm x 94 cm)
		<b>Rear Loading Bin</b>	44"x47"x37" (112 cm x 119 cm x 94 cm)
<b>Safety</b>	Front door: machine will not operate if lockable door is open. Emergency stop button conveniently located. Option to keep loading door locked when in operation. Motor overload protection. Mains Isolator lockable.		

Rotary arm compactors are unique in that they place significant contact pressure and torque on waste to remove the maximum amount of air from it. The Bin RotoPac bins work with either rear or front loading trucks. The RotoPac's rotary arm compaction makes it ideal for quickly compacting large volumes of trash. Built in the US, the RotoPac has over 14 years history of outstanding performance in North America.

Some of the unique characteristics of the original rotary arm compactor are:

1. High compaction ratio (on average greater than 6 to 1) results in up to 80% savings
2. Continuous compaction for high compaction volumes, up to 250 lbs/hour
3. Compaction of wet and dry compactable waste
4. Reduces carbon footprint by fewer collections and less landfill space required
5. Saves space on your facility floor (footprint of 4' x 5')
6. 14 years of quality and durability, low maintenance cost
7. Waste can be fed into the RotoPac by
  - Conveying through the top
  - Gravity feed through a chute
  - Blowing waste into it
  - Manual feed through the loading door
8. Numerous safety features incorporated into its design
9. Requires no supervision or skilled operator, merely input trash and press "Run" button
10. No installation costs, just connect to 240V or 460V 3-phase electrical source